



Premium DFP Oil & Edge Sealed Plywood

Suitable for many forming applications*

- ✓ All Canadian made product
- ✓ With Nox-Crete release agent
- ✓ 6 Ply DFP select grade plywood
- ✓ Exterior waterproof glue
- ✓ Structurally certified to CSA plywood standards by the APA Engineered Wood Association
- ✓ Low formaldehyde N.A.U.F. (less than 0.01 ppm using ASTM large chamber method)
- ✓ From sustainably managed forests - PEFC Chain of Custody
- ✓ Eligible for LEED® & GreenGlobes™ credits, contact us for details
- ✓ Available in 18.5 mm (6 ply) 1220 mm x 2440



chemical solutions to concrete problems

Initial face coat of JL Form Oil 150.

- Environmentally conscious base for release agents containing no harmful additives, distillates or solvents
- Non-staining, light colour
- Safe on rubber liners

Please follow the instructions from your Form Release Oil supplier before use.



Centre to centre span (mm)	Allowable pressure at below deflection limit (kN/m ²)		
	L/180	L/270	L/360
100	159	159	159
150	88	88	88
200	61	61	61
300	37	37	33
400	27	25	19
600	14	9.4	7.1
800	6.7	4.5	3.3

Note:

1. 38 mm or wider supports
2. Face grain perpendicular to supports
3. Consult your design professional on proper use of listed values



Our free [Tolko Product Guide app](#) is available for download. Set yourself up for success by finding the best Tolko lumber, plywood, OSB, and EWP products for each application.



TELEPHONE 250.545.4411
 EMAIL plywood.sales@tolko.com
 WEBSITE www.tolko.com

**TRUE.
TRUSTED.
TOLKO.**