



TOLKO TSTRAND™ PRO
OSB STR 1 SHEATHING

TOLKO TSTRAND™ **ZB**
OSB SHEATHING TREATED

TOLKO T-STRAND™ OSB RESIDENTIAL SHEATHING

At Tolko, we've built our reputation on quality products, customer commitment and an unwavering integrity in all that we do. We strive to partner with our customers, building long-term relationships and helping fuel their ongoing success. We focus on making it easy for our customers to do business with us, providing product quality and consistency and delivering the goods on time, every time.



Tolko T-STRAND™ OSB Residential Sheathing

We know your working conditions are unpredictable but your OSB product performance doesn't have to be. Tolko manufactures both standard and high performance roof and wall sheathing: [Tolko T-STRAND™ OSB Sheathing](#) and [Tolko T-STRAND™ Pro OSB STR 1 Sheathing](#). Both are made with moisture-resistant adhesives and optional zinc borate treatment which means you have one less thing to worry about. Each of these products can lay claim to the following:

- Manufactured to exacting specifications from renewable, recyclable and biodegradable forest resources
- Uses Canadian Aspen wood fiber to produce superior OSB products that are lighter, more durable, and produced to industry standards, meeting customer expectations
- Certified by APA-The Engineered Wood Association
- Backed by industry-standard warranties
- Available with zinc borate treatment for protection from fungal decay and termites
- Competitively priced offering unbeatable value

Tolko T-STRAND™ OSB Sheathing Products offer performance, durability and value. They can make your job easier. We trust our panels to support your needs and perform. We are proud to offer you our Tolko T-STRAND™ OSB roof and wall sheathing products. They are tough. They are tested. They are Tolko.

RESIDENTIAL SHEATHING

		
	GOOD	BETTER
Product application	Roof and wall sheathing	Enhanced roof and wall sheathing
Grading agency	APA	APA
Grading standard	PRS	STR 1
Thickness category¹	3/8", 7/16", 15/32", 1/2", 19/32", 5/8", 23/32", 7/8", 1-1/8"	3/8", 15/32", 1/2", 19/32", 5/8", 23/32"
Lengths¹	6', 8', 9', 10', 12', 14', 16', 24'	6', 8', 9', 10', 12', 14', 16', 24'
Widths¹	4', 8'	4', 8'
Zinc Borate Treatment	Optional ZB TREATED	Optional ZB TREATED
Warranty²	25 years	50 years
• <i>transferable</i>	Yes	Yes
• <i>delamination</i>	25 years	50 years

1 For promotional purposes, lengths and widths are nominal sizes; actual product dimensions comply with U.S. Weights and Measures requirements.

2 Please see unique product warranties for specific details on warranty inclusions and limitations, and always follow the storage and installation instructions. Warranty details available at www.tolko.com.

Sustainable Forest Management

We manufacture our products from renewable, recyclable and biodegradable resources, and our practices are guided by our Forest Management Principles and Environmental Policy.

We also adhere to globally-accepted Sustainable Forest Management (SFM) and Chain of Custody (CoC) standards.



FEATURES

Fastener guide: nailing guide on panel face makes for convenient, easy installation

Moisture resistant edge sealant: blue edge seal protects from moisture penetration

Indoor air quality: contains no added urea-formaldehyde resin (NAUF)

Optional zinc borate treatment: for protection against termites and fungal decay

ZINC BORATE TREATMENT

Zinc borate provides protection against decay fungi/rot and Wood Destroying Organisms (WDO) such as termites, including the Formosan Subterranean Termite.

The treatment is mixed in with the strands, adhesives and wax to provide consistent protection throughout the entire board. There is no need to treat the boards before installation or to reapply treatment after it's been trimmed to size. Zinc borate does not affect the strength properties of the product after treatment.

Our ZB treated products are manufactured at Tolko's Athabasca mill and are approved for use as defined in AWPA U1, Use Category UC2.

APA Product Report PR-N216 confirms that ZB treated T-STRAND OSB meets the performance requirements of PS 2.



WARRANTIES

T-STRAND OSB Sheathing

25-year limited warranty: transferable against delamination.

T-STRAND Pro OSB STR 1 Sheathing

50-year limited warranty: transferable against delamination



TOLKO

Tolko Industries Ltd.
3000 - 28th Street
Vernon, BC V1T 9W9
Canada

TELEPHONE 250.549.5311
EMAIL OSBSales@tolko.com
WEBSITE tolko.com

**TRUE.
TRUSTED.
TOLKO.**

MADE IN CANADA
11.2024

The data and/or information is provided without any representations, warranties or conditions, whether express or implied, statutory or otherwise, including, without any limitation, any representations, warranties or conditions. For more information please visit tolko.com/resources or contact your Tolko Representative.