



## T-STRAND™ PRO OSB SIP FACERS



### Go on, judge these SIPs by their cover

The APA has officially certified T-STRAND Pro OSB SIP Facers to the PR-N614 standard in 19/32" and 23/32" thicknesses. This means that in addition to tilted roof and wall applications where 7/16" thickness is required, our SIP Facers are now certified by the APA for flat roof and flooring applications too.

### BUILD BETTER WITH T-STRAND

Our SIP Facers offer increased moisture resistance with our Blue Edge Seal, which protects against swelling. To ensure our product arrives at your door in the same condition it left our mill, we ship our SIP Facers in a woven-poly bag for extra protection against the elements.

### PANEL MATCHING MADE EASY

Laminating structural insulated panels (SIPs) can feel like you are putting together a puzzle, with OSB boards that never quite seem to fit. To help you get the quality you want, and avoid the stress of finding just the right piece for your project, we offer our dimensionally stable and consistently straight OSB SIP Facers.

### TESTED TO THE HIGHEST STANDARDS

Tested to APA's standards PS2, PR-N610 and PR-N614, these unsanded panels are compatible for laminating with insulating polyurethane (PUR), polyisocyanurate (PIR), and polystyrene (EPS) foam cores.

### T-LINK PRODUCT DISTRIBUTION NETWORK

With the T-LINK Product Distribution Network, our trusted Tolko products are already in your neighborhood and ready to ship. View the T-LINK map to explore all our locations.





Photo courtesy of SIPA



Photo courtesy of SIPA



## T-STRAND PRO OSB SIP FACERS



<b>Product application</b>	SIP Facers for: walls, tilted roofs, flat roofs, flooring
<b>Profile</b>	Square Edge
<b>Grading agency</b>	APA
<b>Grading standard</b>	PS2, PR-N610, PR-N614
<b>Thickness category</b>	7/16", 19/32", 23/32"
<b>Lengths<sup>1,2</sup></b>	12', 16', 24', custom lengths
<b>Widths<sup>1,2</sup></b>	4', 8', custom widths
<b>Moisture-Resistant End Seal</b>	Colour: Tolko Blue
<b>Warranty</b>	Tolko Exclusive Product Warranty
<b>Zinc Borate Treatment</b>	Optional <b>ZB TREATED</b>

- 1 Lengths and widths are nominal sizes; actual product dimensions comply with U.S. Weights and Measures requirements.
- 2 Contact your Tolko Representative for custom lengths and widths.


### WARRANTY

T-STRAND Pro OSB SIP Facers are backed by a limited 25-year warranty against delamination. Full warranty details available at [www.tolko.com](http://www.tolko.com).



### INDOOR AIR QUALITY

This product is CARB, HUD, and EPA TSCA TITLE VI exempt and contains no added urea-formaldehyde resin.



### SUSTAINABLE FOREST MANAGEMENT

We manufacture our products from renewable, recyclable and biodegradable resources, and our practices are guided by our Forest Management Principles and Environmental Policy. We also adhere to globally-accepted Sustainable Forest Management (SFM) and Chain of Custody (CoC) standards.



### ZINC BORATE TREATMENT

Zinc borate provides protection against decay fungi/rot and Wood Destroying Organisms (WDO) such as termites, including the Formosan Subterranean Termite.

The treatment is mixed in with the strands, adhesives and wax to provide consistent protection throughout the entire board. There is no need to treat the boards before installation or to reapply treatment after it's been trimmed to size. Zinc borate does not affect the strength properties of the product after treatment.

Our ZB treated products are manufactured at Tolko's Athabasca mill and are approved for use as defined in AWP A U1, Use Category UC2. APA Product Report PR-N216 confirms that ZB treated T-STRAND OSB meets the performance requirements of PS 2.



Tolko Industries Ltd.  
3000 - 28th Street  
Vernon, BC V1T 9W9  
Canada

TELEPHONE 250.549.5311  
EMAIL [OSBsales@tolko.com](mailto:OSBsales@tolko.com)  
WEBSITE [tolko.com](http://tolko.com)

TRUE.  
TRUSTED.  
TOLKO.



The data and/or information is provided without any representations, warranties or conditions, whether express or implied, statutory or otherwise, including, without any limitation, any representations, warranties or conditions. For more information please visit [tolko.com/resources](http://tolko.com/resources) or contact your Tolko Representative.

11.2024