

Qualified Structural Composite Lumber With Low Formaldehyde Emissions

PR-E720

Revised February 23, 2024

Product: Structural Composite Lumber (SCL) Qualified for Low Formaldehyde Emissions

1. Basis of the product report:
 - APA Custom Product Specification E-720
 - Test method follows the principles of ISO 12460-4, Wood-Based Panels – Determination of Formaldehyde Release, Part 4: Desiccator Method, AS/NZS 4357.0:2022, Structural Laminated Veneer Lumber Part 0: Specifications, and AS/NZS 4357.4:2005 (R2016), Structural Laminated Veneer Lumber, Part 4: Determination of Formaldehyde Emissions
 - JAS 0701 Standard for Laminated Veneer Lumber
 - ASTM D5456-18, D5456-14b, D5456-13, and D5456-09 recognized in the 2021 International Building Code (IBC) and International Residential Code (IRC), 2018 IBC and IRC, 2015 IBC and IRC, and 2012 IBC and IRC, respectively
 - APA Test Reports (see Table 2) and other qualification data

2. Product description:
Structural composite lumber (SCL) defined in this report is any of laminated veneer lumber (LVL), laminated strand lumber (LSL), and oriented strand lumber (OSL). SCL is made with wood strands or veneers of various species oriented or laminated, respectively, with wood fibers primarily oriented along the longitudinal axis of the member in accordance with ASTM D5456 and the in-plant manufacturing standard approved by APA. SCL is available in a variety of grades, thicknesses, and depths.

3. Formaldehyde emission level:
The G-5 rating is a formaldehyde emission level as defined in Table 1. SCL has been qualified for low formaldehyde emissions following the principles of ISO 12460-4 and AS/NZS 4357.4, and the performance requirements of ASTM D5456. SCL products meeting the formaldehyde emission level specified in Table 1 in accordance with the APA Custom Product Specification E-720 are listed in Table 2.

Table 1. Upper formaldehyde emission level for G-5 rating following the principles of ISO 12460-4 and AS/NZS 4357.4^(a)

Average	0.20 mg per liter
Individual specimen	0.30 mg per liter

^(a) SCL products are outside the scope or exempt from CARB ATCM for formaldehyde from composite wood products, EPA's TSCA Title VI Standard for formaldehyde from composite wood, HUD regulation for formaldehyde, and CAN/CSA-O160 for formaldehyde from composite wood products. The tabulated formaldehyde emission level in the G-5 standard is more stringent than the Super E₀ of AS/NZS 4357.0 and F☆☆☆☆ of JAS 0701.

4. Limitations:
 - a) SCL shall be designed and installed in accordance with the applicable provisions of the code and the recommendations provided by the manufacturers.
 - b) SCL trademarked in North America is limited to dry service conditions that result in the average moisture content of sawn lumber of less than 16%.
 - c) SCL products are produced by the manufacturing facilities shown in Table 2 under a quality assurance program audited by APA in accordance with the APA Custom Product Specification E-720.
 - d) This report is subject to re-examination in one year.

5. Identification:

SCL is identified by a label bearing the manufacturer's name and/or trademark, the APA assigned plant number, the product type, the APA logo, means of identifying the date of manufacture, the product report number PR-E720, and the formaldehyde emission rating G-5.

Table 2. Qualified Manufacturing Facilities for Low Formaldehyde Emission^(a)

Manufacturer	Location	Mill Number	Product Type	APA Test Report ^(b)
Boise Cascade Wood Products, LLC	Lena, LA	1106	LVL	T2015P-32
Boise Cascade Wood Products, LLC	White City, OR	1110	LVL	T2015P-32
Boise Cascade Wood Products, LLC	Thorsby, AL	1086	LVL	T2020P-07
Murphy Engineered Wood	Sutherlin, OR	1089	LVL	T2017P-22
PWT	Burlington, WA	1047	LVL	T2010Q-08
PWT	Golden, BC	1066	LVL	T2020P-08
PWT	Wilmington, NC	1071	LVL	T2020P-08
Roseburg Forest Products Co.	Chester, SC	1125	LVL	T2021P-27
Roseburg Forest Products Co.	Riddle, OR	1055	LVL	T2012Q-38
Tolko Industries Ltd.	Slave Lake, AB	1094	LSL	T2019P-11

^(a) This product report is applicable to uncoated SCL.

^(b) Reports for the required periodic confirmation tests are not listed.

APA – *The Engineered Wood Association* is an approved national standards developer accredited by American National Standards Institute (ANSI). APA publishes ANSI standards and Voluntary Product Standards for wood structural panels and engineered wood products. APA is an accredited certification body under ISO/IEC 17065 by Standards Council of Canada (SCC), an accredited inspection agency under ISO/IEC 17020 by International Code Council (ICC) International Accreditation Service (IAS), and an accredited testing organization under ISO/IEC 17025 by IAS. APA is also an approved Product Certification Agency, Testing Laboratory, Quality Assurance Entity, Validation Entity, and Product Evaluation Entity by the State of Florida, and an approved testing laboratory by City of Los Angeles.

**APA – THE ENGINEERED WOOD ASSOCIATION
HEADQUARTERS**

7011 So. 19th St. • Tacoma, Washington 98466
Phone: (253) 565-6600 • Fax: (253) 565-7265 • Internet Address: www.apawood.org

PRODUCT SUPPORT HELP DESK

(253) 620-7400 • *E-mail Address:* help@apawood.org

DISCLAIMER

APA Product Report® is a trademark of APA – *The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. No warranties, express or implied, including as to fitness for a particular purpose, are made regarding this report. Neither APA nor its members shall be liable, or assume any legal liability or responsibility, for damages, direct or indirect, arising from the use, application of, and/or reference to opinions, findings, conclusions or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility for product performance or designs as actually constructed.