

**Tolko Zinc-Borate Treated OSB**  
**Tolko Industries Ltd.**

**PR-N216**

Revised February 13, 2024

Products: Tolko Zinc-Borate Treated OSB  
Tolko Industries Ltd., P.O. Box 39, Vernon BC V1T 6M1, Canada  
(250) 545-4411  
[www.tolko.com](http://www.tolko.com)

1. Basis of the product report:
  - 2021, 2018, 2015, and 2012 International Building Code (IBC): Section 104.11 Alternative materials
  - 2021, 2018, 2015, and 2012 International Residential Code (IRC): Section R104.11 Alternative materials
  - PS 2-18, Performance Standard for Wood Structural Panels
  - APA Report T2017P-44 and other qualification data
2. Product description:

Tolko Zinc-Borate treated OSB is manufactured in accordance with the in-plant manufacturing standard approved by APA. The OSB panel is manufactured with wood flakes, adhesive, wax, and zinc borate, which is added for decay and insect resistance to a retention level equivalent to that specified in the American Wood Protection Association (AWPA) Standard T1 and to that specified as Hazard Class H2 in the Australia – New Zealand standard AS/NZS 1604.2:2021. The efficacy of the preservative treatment is outside the scope of this report and the APA certification program. Tolko Zinc-Borate treated OSB meets the performance requirements of PS 2, and is edge sealed and available in thicknesses from 3/8 to 1-1/8 inches.
3. Design properties:

Tolko Zinc-Borate treated OSB panels meet the design properties specified in APA *Panel Design Specification*, Form D510 ([www.apawood.org/resource-library](http://www.apawood.org/resource-library)) for the Span Rating shown in the trademark.
4. Product installation:

Tolko Zinc-Borate treated OSB recognized in this report shall be installed in accordance with recommendations provided by the manufacturer ([www.tolko.com](http://www.tolko.com)) and APA *Engineered Wood Construction Guide*, Form E30 (see link above). The maximum span shall be in accordance with the Span Rating shown in the trademark.
5. Fire-resistant construction:

Wood structural panels that are not treated with fire retardant chemicals have been shown to meet a Class III (or C) category for flame spread. Unless otherwise specified, fire-resistant construction shall be in accordance with the recommendations published in APA *Fire-Rated Systems*, Form W305 (see link above).
6. Limitations:
  - a) Tolko Zinc-Borate treated OSB recognized in this report shall be used in a design span not exceeding the span rating shown in the trademark.
  - b) Tolko Zinc-Borate treated OSB is limited to use in interior above-ground applications consistent with the recommendations provided by the manufacturer.

- c) Tolko Zinc-Borate treated OSB is limited to dry service conditions where the average equilibrium moisture content of sawn lumber is less than 16%.
  - d) Tolko Zinc-Borate treated OSB is produced by Tolko Industries at their facility in Slave Lake, Alberta, Canada under a quality assurance program audited by APA. The efficacy of the preservative treatment is outside the scope of this report and the APA certification program.
  - e) This report is subject to re-examination in one year.
7. Identification:  
Tolko Zinc-Borate treated OSB panels described in this report are identified by a label or stamp bearing the manufacturer's name and/or trademark (Tolko), the APA assigned plant number (514), the product thickness and span rating, the APA logo, the report number PR-N216, and a means of identifying the date of manufacture.

APA – *The Engineered Wood Association* is an approved national standards developer accredited by American National Standards Institute (ANSI). APA publishes ANSI standards and Voluntary Product Standards for wood structural panels and engineered wood products. APA is an accredited certification body under ISO/IEC 17065 by Standards Council of Canada (SCC), an accredited inspection agency under ISO/IEC 17020 by International Code Council (ICC) International Accreditation Service (IAS), and an accredited testing organization under ISO/IEC 17025 by IAS. APA is also an approved Product Certification Agency, Testing Laboratory, Quality Assurance Entity, Validation Entity, and Product Evaluation Entity by the State of Florida, and an approved testing laboratory by City of Los Angeles.

**APA – THE ENGINEERED WOOD ASSOCIATION  
HEADQUARTERS**

7011 So. 19<sup>th</sup> St. ▪ Tacoma, Washington 98466  
Phone: (253) 565-6600 ▪ Fax: (253) 565-7265 ▪ Internet Address: [www.apawood.org](http://www.apawood.org).

**PRODUCT SUPPORT HELP DESK**  
(253) 620-7400 ▪ E-mail Address: [help@apawood.org](mailto:help@apawood.org)

**DISCLAIMER**

APA Product Report® is a trademark of APA – *The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. No warranties, express or implied, including as to fitness for a particular purpose, are made regarding this report. Neither APA nor its members shall be liable, or assume any legal liability or responsibility, for damages, direct or indirect, arising from the use, application of, and/or reference to opinions, findings, conclusions or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility for product performance or designs as actually constructed.