



PREMIUM DFP Oil & Edge Sealed Plywood

Suitable for many forming applications*

- ✓ All Canadian made product
- ✓ With Nox-Crete release agent
- ✓ 6 Ply DFP select grade plywood
- ✓ Exterior waterproof glue
- ✓ Structurally certified to CSA plywood standards by the APA Engineered Wood Association
- ✓ Low formaldehyde N.A.U.F. (less than 0.01 ppm using ASTM large chamber method)
- ✓ From sustainably managed forests - PEFC Chain of Custody
- ✓ Eligible for LEED® & GreenGlobes™ credits, contact us for details
- ✓ Available in 18.5 mm (6 ply) 1220 mm x 2440



chemical solutions to concrete problems

Initial face coat of JL Form Oil 150.

- Environmentally conscious base for release agents containing no harmful additives, distillates or solvents
- Non-staining, light colour
- Safe on rubber liners

Please follow the instructions from your Form Release Oil supplier before use.



Centre to centre span (mm)	Allowable pressure at below deflection limit (kN/m ²)		
	L/180	L/270	L/360
100	159	159	159
150	88	88	88
200	61	61	61
300	37	37	33
400	27	25	19
600	14	9.4	7.1
800	6.7	4.5	3.3

Note:

1. 38 mm or wider supports
2. Face grain perpendicular to supports
3. Consult your design professional on proper use of listed values

* Please note: This product is not intended for use where a high visual quality surface is desired. Knots and face grain outline may transfer to surfaces.



Our free [Tolko Product Guide](#) app is available for download. Set yourself up for success by finding the best Tolko lumber, plywood, OSB, and EWP products for each application.



The information contained herein is assumed to be correct at the time of printing, but is not guaranteed by the Company, distributor or publisher and should be verified with Tolko Industries Ltd.

TELEPHONE 250.545.4411
 EMAIL plywood.sales@tolko.com
 WEBSITE www.tolko.com

TRUE.
 TRUSTED.
 TOLKO.