



T-TEC PREMIUM FLOORING



Simply everything you really need in PREMIUM FLOORING AND ROOFING.

Tolko T-TEC PREMIUM FLOORING is preferred by builders for premium subfloor applications. Dual stamped with APA Sturd-I-Floor and Structural 1 certification¹ this strand-based composite wood panel boasts incomparable cross-panel stiffness and strength and is also suitable for roofing applications where required. T-TEC PREMIUM FLOORING is engineered to outperform the industry's most advanced flooring panels in nail retention, moisture resistance and durability. You can be confident in our T-TEC PREMIUM FLOORING with a lifetime limited warranty and no-sand guarantee we always stand behind.

BENEFITS OF T-TEC PREMIUM FLOORING

- ✓ Backed by a lifetime limited warranty and performance guarantee that Tolko always stands behind
- ✓ 500-day no-sand guarantee
- ✓ Significantly reduced callbacks
- ✓ Industry leading anti-edge swell performance and guaranteed to stand up to rigorous building conditions
- ✓ Fully sanded, smoother surface and ready for direct application of resilient flooring, saving time and money on your project
- ✓ Manufactured with 100% MDI resin resulting in incomparable durability and industry leading weather and moisture resistance
- ✓ Tongue-and-Groove edges for ease of installation
- ✓ Unbeatable fastener holding
- ✓ Advanced cross-panel stiffness and strength produces stronger, stiffer, quieter floors without the bounce often seen in standard floors
- ✓ Each panel is packaged face up for installation efficiency

CERTIFIED FOR ROOFING APPLICATIONS

- ✓ Dual stamped with APA Sturd-I-Floor and Structural 1 certification, verifying exceptional cross-panel stiffness and strength for both high end residential and commercial flooring and roofing
 - Sturd-I-Floor stamp confirms approval for single layer floor applications under carpet and pad
 - STR 1 certification allows for use in roofing applications where required, in both T&G and Square Edge profiles
- ✓ Approved for roofing applications in both T&G and square edge profiles




ABOUT TOLKO T-TEC

All T-TEC Products are structurally rated and fully engineered, providing the best performance and consistency in the market. Stop worrying about your materials and focus only on your job. When you choose T-TEC you choose top quality, industry leading solutions.

PREMIUM FLOORING AND ROOFING



Specifications	
Product application	PREMIUM FLOORING AND ROOFING
Grades ¹	Dual Stamped Sturd-I-Floor and STR 1
Grading agency	APA
Grading standard	US PS2-18 and CAN CSA-O325 Certified
Surface finish	Fully sanded
Profile	T&G Square Edge available upon request
Thickness category ²	19/32", 23/32", 7/8", 1-1/8"
Lengths ²	8', 10', 12'
Widths ²	4' Full and Scant face available
Warranty ³	Lifetime Limited Warranty
• transferable	Yes
• delamination	Yes
• no-sand	500 Day



WARRANTY

Tolko T-TEC PREMIUM FLOORING will not require sanding due to moisture absorption and edge swell during installation for a period of 500 days and is warranted against delamination for the lifetime of the structure.

CONSISTENT QUALITY

Each run of T-TEC PREMIUM FLOORING is inspected for strength properties, surface quality and dimensional precision to ensure every order is consistent and lives up to the Tolko name.



BETTER PERFORMANCE

Greater cross-panel stiffness, strength, and moisture resistance than standard PS2 OSB and Fir Plywood.

PACKAGING

Protected with cardboard side covers to protect T&G edges and a top-line improved appearance with woven poly bags providing shroud protection on the job site.

MOISTURE RESISTANT EDGE SEALANT

Burnt Sienna colored edge seal protects from moisture penetration.

INDOOR AIR QUALITY

This product is CARB, HUD, and EPA TSCA TITLE VI exempt and contains no added urea-formaldehyde resin.

SUSTAINABLE FOREST MANAGEMENT


We manufacture our products from renewable, recyclable and biodegradable resources, and our practices are guided by our Forest Management Principles and Environmental Policy. We also adhere to globally-accepted Sustainable Forest Management (SFM) and Chain of Custody (CoC) standards.

Notes

1. Currently pending Structural 1 certification.
2. For promotional purposes, lengths and widths are nominal sizes; actual product dimensions comply with U.S. Weights and Measures requirements.
3. See unique product warranties for specific details on warranty inclusions and limitations, and always follow the storage and installation instructions. Warranty details available at www.tolko.com.



Our free Tolko Product Guide app is available for download. Set yourself up for success by finding the best Tolko lumber, plywood, OSB, and EWP products for each application.



Tolko Industries Ltd.
3000 - 28th Street
Vernon, BC V1T 9W9
Canada

TELEPHONE 250.549.5311
EMAIL OSBSales@tolko.com
WEBSITE tolko.com



The information contained herein is assumed to be correct at the time of printing, but is not guaranteed by the Company, distributor or publisher and should be verified with Tolko Industries Ltd.

TRUE.
TRUSTED.
TOLKO.