

# TOLKO

## STORAGE AND HANDLING GUIDE

### TOLKO LAMINATED STRAND LUMBER PRODUCTS



**TRUE.  
TRUSTED.  
TOLKO.**

Tolko Marketing and Sales  
3000 - 28th Street  
Vernon, BC V1T 9W9  
Tel 250.545.4411 - Fax 250.550.2558

Published: November 21, 2023

[WWW.TOLKO.COM](http://WWW.TOLKO.COM)

## INTRODUCTION

Proper storage and handling of engineered wood products (EWP) including T-TEC LSL and Tolko LSL Industrials is required to protect the products during distribution and at the jobsite. APA – The Engineered Wood Association recommends the following storage and handling practices for EWP products. For full details on proper storage and handling, refer to *APA Technical Note: Proper Storage and Handling of I-Joists and LVL, Form E705* available at [www.apawood.org](http://www.apawood.org).

## SAFE HANDLING DURING DISTRIBUTION

1. Bundle wrap can be slippery. Avoid walking on wrapped bundles. Stacks of product may be unstable or slippery, especially when wet. Avoid walking on the material.
2. Follow good forklift safety procedures when handling T-TEC LSL and Tolko LSL Industrials at the yard.
3. Store longest material lowest to the ground.
4. When handling with a crane, pick up the load using a spreader if necessary to minimize handling stresses.
5. Post and follow load limits on storage racks.

## STORAGE DURING DISTRIBUTION

1. Keep wrapped to protect from weather.
2. Use stickers to separate bundles.
3. Use stickers every 8 feet and maintain vertical alignment of the stickers.
4. Do not store T-TEC LSL and Tolko LSL Industrials in direct contact with the ground.
5. For optimal moisture protection, keep at least 12 inches up from the ground.
6. To protect from dirt and weather, delay unwrapping the bundles until the time of the installation or cut-up for delivery.
7. Take care to avoid forklift damage. If the ground is unlevel in the storage area, reduce forklift speed to avoid “bouncing” the load.
8. When handling with a crane, pick up the load using a spreader if necessary to minimize handling stresses.
9. Maintain stack height within safe limits.
10. Do not stack other material on top of T-TEC LSL and Tolko LSL Industrials.

## PROPER HANDLING AT THE JOBSITE

1. Do not drop the product off the delivery truck. Best practice is to use a forklift or boom.
2. Store on level, well-drained area.
3. Keep on stickers spaced every 8’ and at least every 6” off the ground at the jobsite.
4. Keep material covered to protect from weather.
5. Do not stack other material on top of the product.
6. Never use or try to repair damaged products. If defective material is discovered prior to or during installation, cease installation and contact the supplier.

## MOISTURE EFFECTS

T-TEC LSL and Tolko LSL Industrials products are manufactured under carefully controlled conditions that assure they are dry. Moisture content can be affected by humidity, exposure to wetting and drying conditions. While T-TEC LSL and Tolko LSL Industrials products are engineered to withstand normal exposure, excessive exposure to moisture may lead to dimensional change.

If moisture is present, mold, mildew and wood decay fungi may grow on any engineered wood products, thus it is important to properly store T-TEC LSL and Tolko LSL Industrials to control exposure to moisture. Moisture increase is expected under normal construction situations and does not adversely affect the performance of the products if good building practices are followed to minimize exposure and to provide proper conditions for the products to re-equilibrate to dry conditions.

**Reference:** *APA Technical Note: Proper Storage and Handling of I-Joists and LVL, Form E705* available at [www.apawood.org](http://www.apawood.org).



Refer to product specific technical guides available at [www.tolko.com](http://www.tolko.com) for T-TEC LSL installation instructions.



## ENGINEERED WOOD DESIGN SOFTWARE

Tolko offers authorized customers access to engineered wood design software by Calculated Structured Design (CSD) and MiTek.

To become a Tolko authorized user, please contact your Tolko EWP sales representative at:

### EWP Sales

Phone: 250-549-5311

Email: [EWPsales@tolko.com](mailto:EWPsales@tolko.com)

Website: [www.tolko.com/ewp](http://www.tolko.com/ewp)



**TRUE. TRUSTED. TOLKO.**

[WWW.TOLKO.COM](http://WWW.TOLKO.COM)